

Reusing Page Content

How to use include tags to reuse pages and page content within other pages.

You may find that you want to include the same block of content in multiple places. You could copy and paste that content into multiple pages but then, if that content needs to be changed, you'd have to update it multiple times across different pages. By using include tags you can include entire other pages and also include single blocks of content from other pages.

Note that the include behaviour is non-recursive so including will only work to a single level. This ensures performance and prevents users from breaking pages by creating include loops.

Include Tags

To include the content of a page within another you can use the following syntax:

```
{{@page_id}} or {{@page_id#content_id}}
```

You simply enter that in the page editor and then, when the page is viewed, the content will be dynamically be fetched. This means you can update the referenced content and it will show the same changes on any page the content is included within.

Easily Grabbing the Syntax

Finding the id of a page can be difficult so a quick and easy way to find include tags is built-in. View a page with some content you want to re-use. Use your mouse to select some content and you will see a popup appear. By default this contains a direct link to that content. If you click the link icon on the left it will switch to show you the include tag for that content. Simply copy that and place it in another page.

Remove the `#` and content id to include the whole content of the page instead of just a single block.

Forcing Content IDs

When including a specific block of content the id of the block is used (part after the hash). By default these are generated when you save a page. If you are using the WYSIWYG editor the id will stay the same unless the block is removed or re-formatted. In the markdown editor it changes with every save based on the content so while it may remain the same there's a good chance an ID can change therefore it's recommended to force an ID if you're using the content for includes.

Note: All ID values must start with "bkmrk" to avoid being overwritten.

WYSIWYG Editor

In the WYSIWYG editor you can force an ID by going into the source code view and adding it manually:

